

Strip-Brite 229 - Aircraft and Industrial Paint Remover

DESCRIPTION

Strip-Brite 229 is a phenolic-type paint remover formulated to strip tough coatings from many surfaces, including aluminium. Strip-Brite 229 is a pH neutral gel that clings to vertical surfaces. It will not cause hydrogen embrittlement to high strength steel as per MIL-R-81294 test, is non-flammable and formulated with a superior detergent system to allow for easy rinsing.

DIRECTIONS

Strip-Brite 229 should be used full strength at 65 - 85 °F. Apply a thick and even coat with a non-atomizing spray or brush. Allow sufficient time for paint to loosen and then agitate with a stiff bristle brush. Check if paint has been completely removed; if not, apply a second thin coat of Strip-Brite 229. When stripping is complete, wash with cold or warm water at 50 psi or higher.

CAUTION

Strip-Brite 229 contains Methylene Chloride and Phenol. Use only in well ventilated areas. Avoid ingestion, prolonged inhalation, and contact with skin, eyes and clothing. Use a face shield and solvent resistant clothing when handling or working with this product. Plexiglas and rubber should be protected from contact with Strip-Brite 229. Other surface materials may also be incompatible with this stripper; test a small area to ensure proper results.

NOTICE

To our best knowledge, the information and recommendations contained herein are accurate and reliable. However, this information and our recommendations are furnished without warranty, expressed or implied. The manufacturer's sole obligation shall be to replace the portion of the product proven to be defective. The seller or manufacturer shall not be liable for any loss, damage or injury from the use or possession of this product.